

FL 105H

Quick and easy to use - now even better



TECHNICAL DATA	FL 105H
Self-levelling	horizontal
Self-levelling range	±5°
Laser class	2
Visible laser beam	red
Accuracy horizontal	1,0 mm / 10 m
Working range with receiver Ø	
with FR 45	600 m
with FR 77-MM	300 m
Automatic TILT function	yes
VWS function	yes
Rotating speed rpm	800
Operating time	36 h NiMH
Temperature range	-20° to +50°C
Dust / water protection	IP 65

FEATURES
Self-levelling horizontal rotating laser
· 3 buttons for user-friendly functionality
· Working range 600 m diameter
· Dust / water protection IP 65
· Automatic TILT alarm function
· VWS function (Vibration-Wind-Security)
· Auto-shut-off when out of level

SUPPLIED WITH
FL 105H (LC 2) + FR 45
ART.-NO. 212001
· Receiver FR 45 with clamp for levelling staff
· Rechargeable battery and charger
· Battery compartment for alkaline batteries
· Container

SUPPLIED WITH
FL 105H (LC 2) + FR 77-MM
ART.-NO. 212078
· Receiver FR 77-MM with clamp for levelling staff
· Rechargeable battery and charger
· Battery compartment for alkaline batteries
· Container

SUPPLIED WITH
FL 105H (LC 2) + FR-DIST 30
ART.-NO. 212031
· Receiver FR-DIST 30 with clamp for levelling staff
· Rechargeable battery and charger
· Battery compartment for alkaline batteries
· Container