

Set FMR 700-M/C Machine Control Receiver Set



TECHNICAL DATA		FMR 700-M/C UND 706-M/C	FEATURES	SUPPLIED WITH FMR 700-M/C UND 706-M/C
Accuracy fine		± 2 mm – ± 10 mm	<ul style="list-style-type: none"> · Length of receiving window: 25 cm · Connect to the machine with screw clamps or with strong magnets (both supplied in the kit) · Detects beam from rotating laser levels of any brand · Remote display 	<p>Machine control receiver, built-in rechargeable battery, charger, 12 / 24V-battery cable, remote display with connection cable, hard case</p> <p>Also supplied separately:</p> <ul style="list-style-type: none"> · Machine control receiver FMR 706-M / C, built-in battery, charger, 12 / 24V battery cable, hard case · Remote display with connection cable
Accuracy coarse		± 5 mm – ± 23 mm		
Rechargeable batteries		7,2 V NiMH		
		2500 mAh		
Operating time		40 h		
Charging time		15 h		
Temperature range		-20°C to +50°C		
Dimensions		376 x 180 x 49mm		
Weight		3,1 kg		

FMR 706-M/C (MAGNET AND CLAMP)

ART.-NO. 260550

FRP 707 (WITHOUT MACHINE CONTROL RECEIVER)

ART.-NO. 263000

SET FMR 700-M/C (MAGNET AND CLAMP) + FRP 707

ART.-NO. 260500

