

FMR 800-M /C SET Machine Control Receiver



TECHNICAL DATA	FMR 800-M/C	MACHINE CONNECTION	FEATURES
Beam reception angle	360°	Magnetic connection directly	· Length of receiving window:
Detectable rotating laser speeds rpm	300 - 1200	to the machine	27 cm
Working range class 2-laser	250 m	 Clamp connection to the machine Clamp connection to the machine Will detect the beam from any brand of rotating laser (red) Mast diameter 40–50 mm Dust / water protected metal housing Wireless remote display with suction pad and integrated magnets 	
Working range class 3R-laser	350 m		
Battery recharging time	4 - 5 h		
Automatic power-off, after	60 min.		
Dust / water protection	IP 66		0
	-10 °C to +50 °C		
Operating temperature	-10 °C to +50 °C 370 x 132 x 92 mm		
Dimensions			magnets
Weight (receiver only)	3.95 kg		
BULLDOZER MODE		EXCAVATOR MODE	
Blade tilt		Bucket tilt	
(Receiver movement left / right tilted)		(Receiver movement in longitudinal dir	rection forward / backward tilted)
Accuracy	fine / standard / coarse	Accuracy	fine / standard / coarse
	± 0.5° / ± 1.5° / ± 2.5°		$\pm 0.5^{\circ} / \pm 1.5^{\circ} / \pm 2.5^{\circ}$
Indication LED (left / right sideways)	5	Indication LED, grouped	3
		3 signals: rapid/slow flashing, permane	ent light
Height indication			
(Receiver movement up / down)		Height indication	
Accuracy	fine / standard / coarse	(Receiver movement up / down)	
	± 5 / ± 15 / ± 30 mm	Accuracy	fine / standard / coarse
Indication LED (up / down)	3		± 5 / ± 15 / ± 30 mm
		Indication LED, (up / down) grouped	4
		Extended upper LED for bucket dipping motion	
		SUPPLIED WITH FMR 800-M/C	SUPPLIED WITH FMR 800-M/C SET
		ARTNO. 264500	ARTNO. 264550
		 Machine receiver FMR 800-M / C with built-in rechargeable battery Charger 	 SET Machine receiver FMR 800-M / C with built-in rechargeable battery

· Hard carrying case

· Charger

 Remote display FRD 807 with suction pad and batteries
 Hard carrying case